# Meta results on data-driven control of nonlinear systems

Nima Monshizadeh, Claudio De Persis, and Pietro Tesi

Abstract—This note aims to provide a systematic understanding of direct data-driven control, enriching the existing literature not by adding another isolated result, but rather by offering a comprehensive, versatile, and unifying framework that sets the stage for future explorations and applications in this domain. To this end, we formulate the nonlinear design problem from a high-level perspective as a set of desired controlled systems and propose systematic procedures to synthesize data-driven control algorithms that meet the design requirements specified in the desired set. Various examples are presented to demonstrate the comprehensiveness and adaptability of the proposed approach.

Index Terms—Data-driven control, Nonlinear control systems, Linear Matrix Inequalities.

#### I. Introduction

The ability to harness data to directly influence system design and control strategies represents a significant advancement in control systems research. Conventional methodologies often rely on explicit system identification followed by controller design, a process that may not only be cumbersome but also less effective for complex systems. In contrast, data-driven control offers a promising avenue by enabling the design of controllers directly from raw data, without the intermediary step of system modeling. This approach has become increasingly attractive with advancements and popularization of machine learning algorithms, which have spread through various branches of science and engineering, including automatic control.

The expanding interest in data-driven methodologies is fuelled by their potential to circumvent the limitations of model-based techniques, particularly in the realm of nonlinear systems where a priori given mathematical model may not be available. Nonlinear systems, characterized by their rich dynamics that are not amenable to linear analysis and necessitate a more involved approach to control design. As such, the field has seen diverse data-guided strategies being proposed and tested, ranging from virtual reference control [1], kernel-based design [2], intelligent PID [3] and sampled-data model-free control [4], [5] to data-enabled model predictive control [6], dynamic mode decomposition [8], Koopman design [7], and data-based semidefinite programs [9, Subsection V.B], [10].

The current work belongs to the category of direct datadriven control design aiming to reduce the task of controller design to programs that are stated in terms of data collected from the system. Due to its inherent complexity, the landscape of direct data-driven control for nonlinear systems is fragmented with solutions that often target specific problem settings or system types. Examples include stabilization of bilinear systems [11], [12], polynomial systems [13], [14], rational systems [15], and flat systems [16]. Such specialization is valuable as it provides concrete solutions to the control problems under investigation. Nevertheless, there is a compelling need to develop a coherent framework that can address a broader spectrum of control challenges. While the focus on particular instances or system models has driven substantial contributions, a unified approach could illuminate the underlying principles, fostering even greater advancements in the field.

Recognizing the need and the benefits for such a unified approach, this note introduces a meta-framework for a direct data-driven design of nonlinear control systems. We, first, embed the design specifications in a set of desired closed-loop systems. Subsequently, we establish systematic procedures to obtain the control gain from the system data such that the design specifications are enforced. The controller parametrization in [9], [17], serves as a pivotal element of the meta procedures laid out in this manuscript. The proposed approach distinguishes itself by its comprehensiveness and unifying aspects, aiming not only to incorporate several existing results into a cohesive framework but also to extend their applicability to obtain new results in the domain of nonlinear direct datadriven control. Furthermore, the proposed results provide a systematic treatment of deriving control algorithms from data. This systematic procedure ensures that diverse design objectives, such as stabilization, performance, and input-output properties can be seamlessly adapted and integrated into the design.

The structure of the manuscript is as follows. The problem of interest is formulated in Section II. The solution to this problem is provided in Subsection III-A. Necessity of a key assumption is discussed in Subsection III-B. Extensions of the results to open systems are provided in Subsection III-C. Finally, the manuscript closes with conclusions in Section IV.

#### II. PROBLEM SETUP

Consider a nonlinear system of the form

$$x^+ = f(x) + Bu$$

where  $x \in \mathbb{R}^n$ ,  $f: \mathbb{R}^n \to \mathbb{R}^n$  is locally Lipschitz, and  $B \in \mathbb{R}^{n \times m}$ . The notation  $x^+$  denotes either the state variables shifted in time or the time derivative of the states depending on the setting (i.e. continuous or discrete time). While the map f and the input matrix B are assumed to be unknown, we assume that there exists a *known* library of nonlinear functions, denoted by  $Z: \mathbb{R}^n \to \mathbb{R}^s$ ,  $s \geq n$ , such that f can be written as AZ(x) for some matrix  $A \in \mathbb{R}^{n \times s}$ . Hence, the nonlinear system is represented by

$$x^{+} = AZ(x) + Bu. (1)$$

N. Monshizadeh and C. De Persis are with the Engineering and Technology Institute, University of Groningen, 9747AG, The Netherlands (e-mail: n.monshizadeh@rug.nl, c.de.persis@rug.nl).

P. Tesi is with DINFO, University of Florence, 50139 Florence, Italy (e-mail: pietro.tesi@unifi.it).

Note that we allow  $Z(\cdot)$  to be as exhaustive as necessary and potentially include functions that do not appear in f. To avoid redundancy in the representation, we assume that the matrix B has full column rank.

Under a nonlinear state feedback protocol u = KZ(x),  $K \in \mathbb{R}^{m \times s}$ , the closed-loop system admits the form

$$x^+ = F_K Z(x)$$

with  $F_K := A + BK$ ,  $F_K \in \mathbb{R}^{n \times s}$ . The aim of the nonlinear controller is to impose some desired stability/performance properties on the closed-loop system. Rather than fixing a particular choice of a closed-loop, we consider a set of desired closed-loop dynamics. A set of desired closed-loop systems can be parametrized as

$$x^{+} = F^{\star}Z(x), \qquad F^{\star} \in \mathcal{F}_{\text{des}}, \tag{2}$$

where any matrix  $F^* \in \mathcal{F}_{des}$  is such that the closed-loop vector field  $F^*Z(x)$  meets the design criteria. The next example illustrates this parametrization.

**Example 1** First, consider the case of a linear discrete-time system, namely Z(x) = x. Suppose that the design criterion is to geometrically stabilize the closed-loop system with a specified rate of decay. This gives rise to

$$\mathcal{F}_{\text{des}} = \{ F : \exists P > 0, \quad \rho F^T P F - P < 0 \},$$

where the parameter  $\rho > 1$  can be chosen to control the decay rate of the solutions. In case of nonlinear systems, with the same design criterion, the set  $\mathcal{F}_{\mathrm{des}}$  modifies to

$$\mathcal{F}_{\text{des}} = \{ F : \exists V \in \mathcal{V}, \quad \rho V(FZ(x)) \} \leq V(x), \ \forall x \in \mathbb{R}^n \},$$

where V denotes the set of Lyapunov functions satisfying

$$\alpha \|x\|^2 \le V(x) \le \beta \|x\|^2$$

for some  $\alpha, \beta > 0$ . Restricting to quadratic Lyapunov functions, i.e.  $V(x) = x^T P x$ , the latter can be written more explicitly as

$$\mathcal{F}_{\text{des}} = \{ F : \exists P > 0, \\ \rho Z(x)^T F^T P F Z(x) - x^T P x < 0, \forall x \in \mathbb{R}^n \}.$$

Clearly, in the above examples, any  $F^{\star} \in \mathcal{F}_{des}$  is such that the closed-loop system (2) meets the design criterion.

The central problem of this note is formulated below.

**Problem 1** Given  $\mathcal{F}_{\mathrm{des}}$ , design a state feedback protocol u=KZ(x) such that the resulting closed-loop system belongs to the set of desired systems in (2). Equivalently, find K such that  $A+BK\in\mathcal{F}_{\mathrm{des}}$ .

Clearly, not any desired closed-loop system is attainable. Noting (1), a closed-loop system  $x^+ = FZ(x)$  is attainable if and only if there exists K such that A + BK = F. Hence, the set of attainable, not necessarily desired, closed-loop system can be parametrized by the following set:

$$\mathcal{F}_{\mathrm{att}}^{\mathrm{model}} := \{ F : \mathrm{im}(A - F) \subseteq \mathrm{im}\, B \}.$$
 (3)

Notice that Problem 1 is solvable if and only if  $\mathcal{F}_{des} \cap \mathcal{F}_{att}^{model} \neq \emptyset$ .

# III. MAIN RESULTS

#### A. Solutions to Problem 1

We take a data-driven approach towards this problem. We collect input-state data from the system and store them in matrices  $U_0 \in \mathbb{R}^{m \times N}$ ,  $Z_0 \in \mathbb{R}^{s \times N}$ , and  $X_1 \in \mathbb{R}^{n \times N}$  satisfying

$$X_1 = AZ_0 + BU_0. (4)$$

The equality (4) is consistent with (1); specifically,  $U_0$  corresponds to the input samples,  $Z_0$  corresponds to the library  $Z(\cdot)$  evaluated at the state samples, and  $X_1$  stores the shifted in time (or time-derivative) state samples. Note that working with either the model or the data does not affect the choice or formulation of  $\mathcal{F}_{\text{des}}$ . On the other hand, since we aim to use the collected data as a proxy for the model, we require a counterpart of (3) in terms of data. To this end, we define

$$\mathcal{F}_{\rm att}^{\rm data} := \left\{ F : \operatorname{im} \begin{bmatrix} F \\ I_s \end{bmatrix} \subseteq \operatorname{im} \begin{bmatrix} X_1 \\ Z_0 \end{bmatrix} \right\}. \tag{5}$$

The following lemma states several properties of this set and its relation to the set of attainable closed-loop models  $\mathcal{F}_{\rm att}^{\rm model}$ .

**Lemma 2** The set  $\mathcal{F}_{\mathrm{att}}^{\mathrm{data}}$  has the following properties:

- (i) The set  $\mathcal{F}_{\mathrm{att}}^{\mathrm{data}}$  is nonempty if and only if  $Z_0$  has full row rank.
- $(ii) \ \mathcal{F}_{\rm att}^{\rm data} \subseteq \mathcal{F}_{\rm att}^{\rm model}.$
- (iii)  $\mathcal{F}_{
  m att}^{
  m data} = \mathcal{F}_{
  m att}^{
  m model}$  if and only if the data matrix  $\begin{bmatrix} Z_0 \\ U_0 \end{bmatrix}$  has full row rank

**Proof.** Item (i): If  $\mathcal{F}_{\mathrm{att}}^{\mathrm{data}}$  is nonempty, then  $\mathrm{im}\,I_s\subseteq\mathrm{im}\,Z_0$  and thus  $Z_0$  has full row rank. Conversely, if  $Z_0$  has full row rank, then  $X_1Z_0^+\in\mathcal{F}_{\mathrm{att}}^{\mathrm{data}}$  for any right inverse  $Z_0^+$  of  $Z_0$ . Item (ii): Observe that the set  $\mathcal{F}_{\mathrm{att}}^{\mathrm{model}}$  in (3) can be equivalently written

$$\mathcal{F}_{\text{att}}^{\text{model}} = \left\{ F : \text{im} \begin{bmatrix} F \\ I_s \end{bmatrix} \subseteq \text{im} \begin{bmatrix} A & B \\ I_s & 0 \end{bmatrix} \right\}. \tag{6}$$

The subspace inclusion  $\mathcal{F}_{\rm att}^{\rm data}\subseteq\mathcal{F}_{\rm att}^{\rm model}$  then holds due to

$$\operatorname{im} \begin{bmatrix} X_1 \\ Z_0 \end{bmatrix} = \operatorname{im} \begin{bmatrix} A & B \\ I_s & 0 \end{bmatrix} \begin{bmatrix} Z_0 \\ U_0 \end{bmatrix} \subseteq \operatorname{im} \begin{bmatrix} A & B \\ I_s & 0 \end{bmatrix}, \qquad (7)$$

where we used (4) to write the first equality. Item (iii): Bearing in mind that  $\begin{bmatrix} A & B \\ I_s & 0 \end{bmatrix}$  has full column rank, the inclusion in (7) can be replaced by equality if and only if the matrix  $\begin{bmatrix} Z_0 \\ U_0 \end{bmatrix}$  has full row rank.

Recall that Problem 1 is solvable if and only if  $\mathcal{F}_{att}^{model} \cap \mathcal{F}_{des} \neq \emptyset$ ; namely, the desired set  $\mathcal{F}_{des}$  and the attainable set  $\mathcal{F}_{att}^{model}$  should at least share a common element. Motivated by the fact that we work directly with the data rather than the model, we replace  $\mathcal{F}_{att}^{model}$  by its data-based subspace  $\mathcal{F}_{att}^{data}$  in the latter solvability condition, which results in the following assumption:

**Assumption 1** It holds that  $\mathcal{F}_{\text{att}}^{\text{data}} \cap \mathcal{F}_{\text{des}} \neq \emptyset$ .

This assumption is sufficient for solvability of Problem 1 since  $\mathcal{F}_{\rm att}^{\rm data}\subseteq\mathcal{F}_{\rm att}^{\rm model}$  by Lemma 2. We will discuss "necessity" of this assumption in Subsection III-B.

We have now the following result:

**Theorem 3** Let Assumption 1 hold and define

$$\mathcal{K} := \left\{ K : \operatorname{im} \begin{bmatrix} F^{\star} \\ I_{s} \\ K \end{bmatrix} \subseteq \operatorname{im} \begin{bmatrix} X_{1} \\ Z_{0} \\ U_{0} \end{bmatrix}, \ F^{\star} \in \mathcal{F}_{\operatorname{des}} \right\}. \tag{8}$$

Then, the set K is nonempty. Moreover, Problem 1 is solvable by the state feedback u = KZ(x) for any  $K \in \mathcal{K}$ .

**Proof.** The fact that the set K is nonemempty follows from Assumption 1 and (5). Now, suppose  $K \in \mathcal{K}$ . Then, we find that

$$\begin{bmatrix} F^* \\ I_s \\ K \end{bmatrix} = \begin{bmatrix} X_1 \\ Z_0 \\ U_0 \end{bmatrix} G,$$
 (9)

for some matrices  $G \in \mathbb{R}^{N \times s}$  and  $F^{\star} \in \mathcal{F}_{\mathrm{des}}$ . We have

$$A + BK = \begin{bmatrix} A & B \end{bmatrix} \begin{bmatrix} I \\ K \end{bmatrix} = \begin{bmatrix} A & B \end{bmatrix} \begin{bmatrix} Z_0 \\ U_0 \end{bmatrix} G = X_1 G = F^*,$$

where the second and last equality follow from (9), and the third one from (4). As  $F^* \in \mathcal{F}_{des}$ , we conclude that (A + $BK) \in \mathcal{F}_{\mathrm{des}}$  and thus the controller KZ(x) solves Problem

Theorem 3 provides a meta-procedure for solving Problem 1 using data:

- 1) Parametrize  $\mathcal{F}_{\mathrm{des}}$  based on the design objective. 2) Find  $F^{\star} \in \mathcal{F}_{\mathrm{des}} \cap \mathcal{F}_{\mathrm{att}}^{\mathrm{data}}$ . Namely, find  $F^{\star}$  such that  $f^{\dagger}$

$$F^\star \in \mathcal{F}_{\mathrm{des}} \ \ \mathrm{and} \ \ \mathrm{im} \begin{bmatrix} F^\star \\ I_s \end{bmatrix} \subseteq \mathrm{im} \begin{bmatrix} X_1 \\ Z_0 \end{bmatrix}.$$

3) Choose  $K \in \mathcal{K}$ .

Next, we apply the above procedure to a couple of examples.

Example 4 (Stabilization via linearization) As the first example, we consider the control objective of rendering the equilibrium asymptotically stable by stabilizing the linearized dynamics. It is easy to see that the set of desired closedsystems takes the form:

$$\mathcal{F}_{\text{des}} := \{ F : \exists P > 0, \quad FZ'(0)P(FZ'(0))^T - P < 0 \},$$
(10)

where Z' is shorthand notation for the Jacobian of Z. Following the second step of the procedure, we look for  $F^* \in$  $\mathcal{F}_{\rm des} \cap \mathcal{F}_{\rm att}^{\rm data}$  . This gives rise to the following set of constraints:

$$FZ'(0)P(FZ'(0))^{T} - P < 0, \quad P > 0,$$
  
 $F = X_{1}G,$   
 $I_{s} = Z_{0}G.$ 

The aforementioned constraints can be transformed into a LMI through standard change of variables, specifically by defining Y := GZ'(0)P and employing a Schur complement argument. This LMI, obtained systematically, offers a direct extension of the linear stability results [9, Thm. 3].

**Example 5 (Stabilization via nonlinearity cancellation)** Let Z(x) be partitioned as

$$Z(x) = \begin{bmatrix} x \\ Q(x) \end{bmatrix}. \tag{11}$$

where  $Q: \mathbb{R}^n \to \mathbb{R}^{s-n}$  contains all the nonlinear functions in the library. The goal here is to stabilize the nonlinear system by rendering the closed-loop dynamics linear. In this case, the set of desired closed-loop systems is given by

$$\mathcal{F}_{\text{des}} := \{ \begin{bmatrix} \bar{F} & 0 \end{bmatrix} : \exists P > 0, \quad \bar{F}^T P \bar{F} - P \leq 0 \},$$

where the partition is consistent with (11), i.e.  $\bar{F} \in \mathbb{R}^{n \times n}$ . This concludes the first step of the procedure. The second step of the procedure is to search for a matrix  $F^*$  belonging to  $\mathcal{F}_{\mathrm{des}} \cap \mathcal{F}_{\mathrm{att}}^{\mathrm{data}}$  . Clearly, the intersection is given by

$$\mathcal{F}_{\mathrm{des}} \cap \mathcal{F}_{\mathrm{att}}^{\mathrm{data}} = \left\{ \begin{bmatrix} \bar{F} & 0 \end{bmatrix} \in \mathcal{F}_{\mathrm{des}} : \mathrm{im} \begin{bmatrix} \bar{F} & 0 \\ I_s \end{bmatrix} \subseteq \mathrm{im} \begin{bmatrix} X_1 \\ Z_0 \end{bmatrix}, \right\}.$$

This boils down to finding  $\bar{F}, P, G$  satisfying the following constraints:

$$\bar{F}^T P \bar{F} - P \le 0, \quad P > 0,$$
  
 $\begin{bmatrix} \bar{F} & 0 \end{bmatrix} = X_1 G,$   
 $I_s = Z_0 G.$ 

A solution satisfying the above constraints exists under Assumption 1. By Theorem 3, given any feasible solution  $(\bar{F}, P, G)$  to the above constraints, the controller u = KZ(x)with  $K = U_0G$  solves Problem 1, namely the closed-loop system becomes a linear Schur stable system as desired. This coincides with the recent result [17, Thm. 1].

Next, we move away from stabilization and discuss an example with a different control objective.

Example 6 (Nonlinear oscillator design) Consider the planar system

$$x_1^+ = x_2$$
  
 $x_2^+ = f(x_1, x_2) + u$ 

for some  $f: \mathbb{R}^2 \to \mathbb{R}$ . The goal is to design a state-feedback control such that the resulting closed-loop system behaves like a Van der Pol Oscillator in discrete-time, i.e.,

$$\hat{x}_1^+ = \hat{x}_2$$

$$\hat{x}_2^+ = \hat{x}_2 + \mu^2 (\hat{x}_2 - \frac{1}{3}\hat{x}_2^3 - \hat{x}_1)$$

with  $\mu$  satisfying the design constraint  $\mu_{\ell} \leq \mu \leq \mu_{u}$ , for some given lower and upper bound.

In this case, we partition the library Z(x) as

$$Z(x) = \begin{bmatrix} x_1 \\ x_2 \\ x_2^3 \\ Q(x) \end{bmatrix},$$
 (12)

where  $Q: \mathbb{R}^2 \to \mathbb{R}^{s-3}$  contains all functions that can potentially appear in  $f(x_1, x_2)$  other than the first three functions in Z. Note that the first three elements in Z capture all the

<sup>&</sup>lt;sup>1</sup>Such  $F^*$  always exists under Assumption 1.

linear and nonlinear functions appearing in the desired closed-loop dynamics. Then, the set of desired closed-loop systems is given by

$$\mathcal{F}_{\text{des}} = \left\{ \begin{bmatrix} 0 & 1 & 0 & 0_{s-3}^T \\ -\mu^2 & 1 + \mu^2 & -\frac{1}{3}\mu^2 & 0_{s-3}^T \end{bmatrix} : \mu_{\ell} \le \mu \le \mu_u, \right\},\,$$

where the partition is consistent with (12). Now, applying the second step of the procedure results in the following data-based program:

$$\begin{split} & \text{find } \mu \in \mathbb{R}; g_1, g_2, g_3 \in \mathbb{R}^N; G_4 \in R^{N \times (s-3)} \\ & \text{s.t.} \\ & X_1 \begin{bmatrix} g_1 & g_2 & g_3 \end{bmatrix} = \begin{bmatrix} 0 & 1 & 0 \\ -\mu^2 & 1 + \mu^2 & -\frac{1}{3}\mu^2 \end{bmatrix}, \\ & X_1 G_4 = 0, & Z_0 \begin{bmatrix} g_1 & g_2 & g_3 & G_4 \end{bmatrix} = I_s, & \mu \in [\mu_\ell, \mu_u]. \end{split}$$

The controller, as indicated in the third step of the procedure, is given by  $K = U_0 \begin{bmatrix} g_1 & g_2 & g_3 & G_4 \end{bmatrix}$ .

### B. On the necessity of Assumption 1

As observed before, Problem 1 is solvable if and only if  $\mathcal{F}_{\rm att}^{\rm model} \cap \mathcal{F}_{\rm des} \neq \emptyset$ , where  $\mathcal{F}_{\rm att}^{\rm model}$  is given by (3). The following result directly follows from Lemma 2.

Corollary 7 Assume that the matrix  $\begin{bmatrix} Z_0 \\ U_0 \end{bmatrix}$  has full row rank. Then, Problem 1 is solvable if and only if Assumption 1 holds.

The above result states that for "rich" datasets, Assumption 1 is both necessary and sufficient for solving Problem 1. Next, we argue that in case the rank condition in Corollary 7 does not hold, Assumption 1 is still generically "necessary" for solving (the model-based) Problem 1 using only system data in (4). This is true providing that the closed-loop property characterized by  $\mathcal{F}_{\mathrm{des}}$  is "binding". This property is rather mild as formalized below:

**Definition 8** We call  $\mathcal{F}_{\mathrm{des}}$  binding if the following implication holds:

$$F^* \in \mathcal{F}_{\mathrm{des}}, \ v \in \mathbb{R}^s \setminus \{0_s\} \Longrightarrow \exists w \in \mathbb{R}^n \text{ s.t. } F^* + wv^\top \notin \mathcal{F}_{\mathrm{des}}.$$

Note that that the binding property is independent of the data set. The property states that for any  $F^\star \in \mathcal{F}_{\mathrm{des}}$  and nonzero vector v, there exists a vector w such that the perturbed matrix  $F^\star + wv^T$  leaves the desired set  $\mathcal{F}_{\mathrm{des}}$ . The following lemma provides two notable special cases for binding desired sets.

**Lemma 9** The set  $\mathcal{F}_{des}$  is binding if either of the following conditions hold:

- (i)  $\mathcal{F}_{des}$  is finite.
- (ii)  $\mathcal{F}_{des}$  is bounded in some matrix norm.

**Proof.** The first condition is trivial in view of Definition 8. For the second condition, we have

$$\left\| F^{\star} + wv^{T} \right\|_{F}^{2} = \left\| F^{\star} \right\|_{F}^{2} + 2 \underbrace{w^{T} F^{\star} v}_{\geq -\|w\|\|F^{\star}v\|} + \|w\|_{2}^{2} \|v\|_{2}^{2}.$$

Therefore, choosing ||w|| arbitrary large makes  $F^* + wv^T$  unbounded in Frobenius norm and thus in any matrix norm. Hence, there always exists w such that,  $F^* + wv^T \notin \mathcal{F}_{\mathrm{des}}$  implying that  $\mathcal{F}_{\mathrm{des}}$  is binding

The first condition of Lemma 9 states that any  $\mathcal{F}_{\mathrm{des}}$  with a *finite* cardinality is binding. This captures the scenarios where the desired controller coincides with the unique solution (even locally) of an optimization problem as well as the case of prescribing a desired closed-loop system. The second condition states that  $\mathcal{F}_{\mathrm{des}}$  is binding if the norm of the matrices in  $\mathcal{F}_{\mathrm{des}}$  admit a uniform bound, i.e. there exists  $\alpha$  such that  $\|F^*\| \leq \alpha$ ,  $\forall F^* \in \mathcal{F}_{\mathrm{des}}$ .

An example of a property that is not generally binding is the case where the only requirement of  $\mathcal{F}_{\mathrm{des}}$  is asymptotic stability of the equilibrium. In particular, consider the set  $\mathcal{F}_{\mathrm{des}}$  as given by (10) and let  $Z(\cdot)$  be partitioned as (11) with s>n. Consistently, let  $v=\begin{bmatrix}v_1^T & v_2^T\end{bmatrix}^T$  and choose  $v_1^T=-v_2^TQ'(0)$ , where Q' is the shorthand notation for the Jacobian of Q. Clearly, by construction  $v^TZ'(0)=0$ . Therefore, noting (10), for any  $F^\star\in\mathcal{F}_{\mathrm{des}}$ , the perturbed matrix  $F^\star+wv^T$  remains in  $\mathcal{F}_{\mathrm{des}}$  for all  $w\in\mathbb{R}^n$ , which implies that  $\mathcal{F}_{\mathrm{des}}$  is not binding.

Interestingly, the asymptotic stability property becomes binding if some guarantees on the region of attraction are also required in  $\mathcal{F}_{\mathrm{des}}$ . To see this, suppose that the desired closed-loop systems are given by those whose equilibrium is asymptotically stable, and there exists a compact estimate of region of attraction<sup>2</sup>  $\Omega$  with  $\mathcal{B}_{\delta_1} \subseteq \Omega \subseteq \mathcal{B}_{\delta_2}$  for some prescribed  $\delta_1, \delta_2 > 0$ . The lower bound is to exclude arbitrary small estimates of region of attraction, whereas the upper bound enforces compactness of  $\Omega$ . To investigate if this property is binding, given  $v \in \mathbb{R}^s$ , consider the family of systems

$$x^{+} = (F^{\star} + wv^{T})Z(x), \quad w \in \mathbb{R}^{n}, \tag{13}$$

and suppose  $F^* \in \mathcal{F}_{des}$ . Let

$$x_0 := \operatorname{argmax}_{x \in \mathcal{B}_{\delta_1}} |v^T Z(x)|.$$

The value of  $|v^T Z(x_0)|$  is nonzero under the mild assumption that the functions in  $Z(\cdot)$  are linearly independent. Initializing (13) at  $x(0) = x_0$ , we have

$$||x(1)||_{2}^{2} = ||(F^{*} + wv^{T})Z(x_{0})||^{2}$$

$$= Z(x_{0})^{T}F^{*T}F^{*}Z(x_{0}) + 2Z(x_{0})^{T}F^{*T}wv^{T}Z(x_{0})$$

$$+ ||w||^{2} ||v^{T}Z(x_{0})||^{2}.$$

Clearly, as w becomes arbitrarily large, x(1) leaves any given compact set  $\Omega \subseteq \mathcal{B}_{\delta_2}$ , and we find that  $\mathcal{F}_{des}$  is binding in this case

The following result shows that, for binding properties, Assumption 1 is "necessary" for solving Problem 1 using only data.<sup>3</sup>

**Theorem 10** Assume that  $\mathcal{F}_{\mathrm{des}}$  is binding and  $\mathcal{F}_{\mathrm{att}}^{\mathrm{data}} \cap \mathcal{F}_{\mathrm{des}} = \emptyset$ . Suppose that there exists a feedback u = KZ(x) solving

<sup>&</sup>lt;sup>2</sup>An estimate of region of attraction is a forward invariant set such that any solution initialized in this set asymptotically converges to the origin.

<sup>&</sup>lt;sup>3</sup>Such notion of "necessity" is formalized and discussed for various linear control problems in [18].

<sup>&</sup>lt;sup>4</sup>The empty intersection means that Assumption 1 does not hold.

Problem 1, i.e.,  $A+BK\in\mathcal{F}_{\mathrm{des}}$ . Then, there exist  $\bar{A}$  and  $\bar{B}$  consistent with the data, namely  $X_1=\bar{A}Z_0+\bar{B}U_0$  such that  $\bar{A}+\bar{B}K\notin\mathcal{F}_{\mathrm{des}}$ .

**Proof.** By the hypotheses of the theorem, we find that  $A + BK \notin \mathcal{F}_{\text{att.}}^{\text{data}}$ , i.e,

$$\operatorname{im} \begin{bmatrix} A + BK \\ I_s \end{bmatrix} \not\subseteq \operatorname{im} \begin{bmatrix} X_1 \\ Z_0 \end{bmatrix}.$$

Hence,

$$\operatorname{im} \begin{bmatrix} A & B \\ I_s & 0 \end{bmatrix} \begin{bmatrix} I_s \\ K \end{bmatrix} \not\subseteq \operatorname{im} \begin{bmatrix} A & B \\ I_s & 0 \end{bmatrix} \begin{bmatrix} Z_0 \\ U_0 \end{bmatrix},$$

and thus

$$\operatorname{im} \begin{bmatrix} I_s \\ K \end{bmatrix} \not\subseteq \operatorname{im} \begin{bmatrix} Z_0 \\ U_0 \end{bmatrix},$$

or equivalently

$$\ker \begin{bmatrix} Z_0 \\ U_0 \end{bmatrix}^T \nsubseteq \ker \begin{bmatrix} I_s \\ K \end{bmatrix}^T.$$

Therefore, there exists a nonzero vector  $\tilde{v} = \operatorname{col}(\tilde{v}_A, \tilde{v}_B)$ , such that

$$\begin{bmatrix} \tilde{v}_A^T & \tilde{v}_B^T \end{bmatrix} \begin{bmatrix} Z_0 \\ U_0 \end{bmatrix} = 0, \quad \begin{bmatrix} \tilde{v}_A^T & \tilde{v}_B^T \end{bmatrix} \begin{bmatrix} I_s \\ K \end{bmatrix} \neq 0. \tag{14}$$

Due to the first equality, it is easy to see that the matrices  $\bar{A}:=A+w\tilde{v}_A^T$  and  $\bar{B}:=B+w\tilde{v}_B^T$  satisfies the equality  $X_1=\bar{A}Z_0+\bar{B}U_0$  for all  $w\in\mathbb{R}^n$ . Define

$$v^T := \begin{bmatrix} \tilde{v}_A^T & \tilde{v}_B^T \end{bmatrix} \begin{bmatrix} I_s \\ K \end{bmatrix}.$$

The vector v is nonzero due to (14). For any  $w \in \mathbb{R}^n$ , we have  $\bar{A} + \bar{B}K = (A + BK) + wv^T$ . Then, bearing in mind that  $A + BK \in \mathcal{F}_{des}$  and  $\mathcal{F}_{des}$  is binding, there exists  $w \in \mathbb{R}^n$  such that  $\bar{A} + \bar{B}K \notin \mathcal{F}_{des}$ , which completes the proof.

## C. Extension to open systems

In this subsection, we show how the results can be extended to the control law  $u=KZ(x)+K_rr$ , with control gains  $K\in\mathbb{R}^{m\times s},\ K_r\in\mathbb{R}^{m\times m_r}$  and an external input  $r\in\mathbb{R}^{m_r}$  with  $m_r\leq m$ . This results in the open system

$$x^{+} = (A + BK)Z(x) + BK_{r}r \tag{15}$$

The set of desired controlled system can be then parametrized as (cf. (2))

$$x^{+} = \begin{bmatrix} F^{\star} & F_{r}^{\star} \end{bmatrix} \begin{bmatrix} Z(x) \\ r \end{bmatrix}, \quad \begin{bmatrix} F^{\star} & F_{r}^{\star} \end{bmatrix} \in \mathcal{F}_{\text{des}}, \quad (16)$$

where  $\mathcal{F}_{\mathrm{des}}$  now dictates the desired specifications for both matrices  $F \equiv A + BK$  and  $F_r \equiv BK_r$  of the controlled system (15).

**Problem 2** Given  $\mathcal{F}_{\mathrm{des}}$ , design a control law  $u=KZ(x)+K_rr$  such that the resulting controlled system satisfies (16). Equivalently, find K and  $K_r$  such that  $\begin{bmatrix} A+BK & BK_r \end{bmatrix} \in \mathcal{F}_{\mathrm{des}}$ .

By (15), the set of attainable controlled systems is obtained as (cf. (3))

$$\mathcal{F}_{\text{att}}^{\text{model}} := \{ \begin{bmatrix} F & F_r \end{bmatrix} : \text{im} \begin{bmatrix} A - F & F_r \end{bmatrix} \subseteq \text{im} B \}. \tag{17}$$

Next we separate the system matrices from F and  $F_r$  in the above subspace inclusion. It is easy to verify that we can equivalently write the set in (17) as (cf. (6))

$$\mathcal{F}_{\text{att}}^{\text{model}} = \left\{ \begin{bmatrix} F & F_r \\ I_s & 0 \end{bmatrix} \subseteq \text{im} \begin{bmatrix} A & B \\ I_s & 0 \end{bmatrix} \right\}. \tag{18}$$

With the same principle as before, since the system matrices are not available, we work with a purely data-based subspace of  $\operatorname{im}\begin{bmatrix}A&B\\I_s&0\end{bmatrix}$ . This subspace is given by the left hand side of (7). By substituting this data-based subspace in place of  $\operatorname{im}\begin{bmatrix}A&B\\I_s&0\end{bmatrix}$  in (18), we obtain the set (cf. (5))

$$\mathcal{F}_{\rm att}^{\rm data} := \left\{ \begin{bmatrix} F & F_r \end{bmatrix} : \operatorname{im} \begin{bmatrix} F & F_r \\ I_s & 0 \end{bmatrix} \subseteq \operatorname{im} \begin{bmatrix} X_1 \\ Z_0 \end{bmatrix} \right\}. \quad (19)$$

All statements of Lemma 2 holds for the set  $\mathcal{F}_{att}^{data}$  given by (19). Indeed, the inclusion  $\mathcal{F}_{att}^{data} \subseteq \mathcal{F}_{att}^{model}$  holds by noting (7), (18), and (19). The proof of the other two statements are analogous to the arguments provided in the proof of the lemma. Now, the counterpart of Theorem 3 for open systems is provided below:

**Theorem 11** Let Assumption 1 hold with  $\mathcal{F}_{des}$  the set of desired controlled system in (16) and  $\mathcal{F}_{att}^{data}$  given by (19). Define

$$\mathcal{K}_{\text{ext}} := \left\{ \begin{bmatrix} K & K_r \end{bmatrix} : \text{im} \begin{bmatrix} F^* & F_r^* \\ I_s & 0 \\ K & K_r \end{bmatrix} \subseteq \text{im} \begin{bmatrix} X_1 \\ Z_0 \\ U_0 \end{bmatrix}, \\ \begin{bmatrix} F^* & F_r^* \end{bmatrix} \in \mathcal{F}_{\text{des}} \right\}. \tag{20}$$

Then, the set  $\mathcal{K}_{\mathrm{ext}}$  is nonempty. Moreover, Problem 2 is solvable by the control law  $u = KZ(x) + K_r r$  for any  $[K \ K_r] \in \mathcal{K}_{\mathrm{ext}}$ .

**Proof.** The fact that the set  $\mathcal{K}$  is nonempty follows from the assumption and (19). Choose  $\begin{bmatrix} K & K_r \end{bmatrix} \in \mathcal{K}_{\mathrm{ext}}$ . The subspace inclusion in (20) can be split to

$$\operatorname{im} \begin{bmatrix} F^{\star} \\ I_s \\ K \end{bmatrix} \subseteq \operatorname{im} \begin{bmatrix} X_1 \\ Z_0 \\ U_0 \end{bmatrix}, \quad \operatorname{im} \begin{bmatrix} F^{\star}_r \\ 0 \\ K_r \end{bmatrix} \subseteq \operatorname{im} \begin{bmatrix} X_1 \\ Z_0 \\ U_0 \end{bmatrix}.$$

Analogously to the proof of Theorem 3, the first subspace inclusion implies that  $A+BK=F^{\star}$ . By the second subspace inclusion, there exists a matrix  $G_r \in \mathbb{R}^{N \times m_r}$  such that  $F_r^{\star} = X_1 G_r$ ,  $0 = Z_0 G_r$  and  $K_r = U_0 G_r$ . Then, from (4), it follows that  $BK_r = F_r^{\star}$ . The proof is complete noting that  $\left[F^{\star} \quad F_r^{\star}\right] \in \mathcal{F}_{\mathrm{des}}$ .

Theorem 11 provides a meta-procedure for solving Problem 2 using data:

- 1) Specify the set of desired controlled system  $\mathcal{F}_{des}$  based on the design objective.
- 2) Find  $\begin{bmatrix} F^{\star} & F_r^{\star} \end{bmatrix} \in \mathcal{F}_{\text{des}} \cap \mathcal{F}_{\text{att}}^{\text{data}}$ . Namely, find  $F^{\star}$  and  $F_r^{\star}$  such that

$$\begin{bmatrix} F^{\star} & F_r^{\star} \end{bmatrix} \in \mathcal{F}_{\text{des}} \text{ and } \operatorname{im} \begin{bmatrix} F^{\star} & F_r^{\star} \\ I_s & 0 \end{bmatrix} \subseteq \operatorname{im} \begin{bmatrix} X_1 \\ Z_0 \end{bmatrix}.$$

#### 3) Choose $K \in \mathcal{K}$ .

**Example 12 (Model reference control)** Consider a reference nonlinear model

$$x_{\text{ref}}^{+} = \bar{A}\bar{Z}(x_{\text{ref}}) + \bar{B}r, \tag{21}$$

with state  $x_{\text{ref}} \in \mathbb{R}^n$ , input  $r \in \mathbb{R}^{m_r}$ ,  $\bar{A} \in \mathbb{R}^{n \times \bar{s}}$ , and  $\bar{Z} : \mathbb{R}^n \to \mathbb{R}^{\bar{s}}$  capturing the nonlinearities appearing in the reference model. The model reference control (MRC) problem that we consider here is to find the matrices K and  $K_r$  such that the following matching conditions hold:

$$(A + BK)Z(x) = \bar{A}\bar{Z}(x), \quad BK_r = \bar{B}, \quad \forall x \in \mathbb{R}^n,$$

Now, assume that the functions in  $\bar{Z}$  is a subset of those in  $Z^5$  and partition Z as  $Z(x)=\operatorname{col}(\bar{Z}(x),\tilde{Z}(x))$ , with  $\tilde{Z}:\mathbb{R}^n\to\mathbb{R}^{s-\bar{s}}$ . Then, the MRC problem can be equivalently recast as finding the matrices K and  $K_T$  such that

$$A + BK = \begin{bmatrix} \bar{A} & 0 \end{bmatrix}, \quad BK_r = \bar{B}.$$

Hence, the set of desired controlled systems in (16) is specified by the singleton  $\mathcal{F}_{\mathrm{des}} = \{ \begin{bmatrix} F^\star & F_r^\star \end{bmatrix} \}$ , with  $F^\star := \begin{bmatrix} \bar{A} & 0 \end{bmatrix}$  and  $F_r^\star := \bar{B}$ . Next, following the second step of the procedure, the following program solves the nonlinear MRC problem:

find 
$$G_{11} \in \mathbb{R}^{N \times \bar{s}}, G_{12} \in \mathbb{R}^{N \times (s - \bar{s})}, G_2 \in \mathbb{R}^{N \times m_r}$$

$$\begin{bmatrix} \bar{A} & 0 & \bar{B} \\ I_{\bar{s}} & 0 & 0 \\ 0 & I_{s-\bar{s}} & 0 \end{bmatrix} = \begin{bmatrix} X_1 \\ \bar{Z}_0 \\ \tilde{Z}_0 \end{bmatrix} \begin{bmatrix} G_{11} & G_{12} & G_2 \end{bmatrix},$$

where the data matrix  $Z_0$  is partitioned as  $\operatorname{col}(\bar{Z}_0, \tilde{Z}_0)$  consistent to the partitioning of Z. The resulting control law is then given by the third step of the procedure as

$$u = KZ(x) + K_r r = U_0 G_{11} \bar{Z}(x) + U_0 G_{12} \tilde{Z}(x) + U_0 G_2 r.$$

In the special case where the functions in  $Z(\cdot)$  coincides with those in the reference model, the control law reduces to  $u = U_0G_{11}\bar{Z}(x) + U_0G_2r$ . A notable instance of such a special case is MRC in linear systems where  $Z(x) = \bar{Z}(x) = x$ . For linear systems, the resulting controller gains coicide with those reported in [19]–[21].

**Example 13 (Feedback cyclo-passivation)** Consider the system (15) in continuous-time. The problem of interest is to design the controller gains K and  $K_r$  such that the system becomes passive from the input v to a suitably defined output  $y := h(x), h : \mathbb{R}^n \to \mathbb{R}^{m_r}$ . Namely, there should exist a storage function  $S : \mathbb{R}^n \to \mathbb{R}$  such that<sup>6</sup>

$$\frac{\partial S}{\partial x}^{T}(x)(A+BK)Z(x) + \frac{\partial S}{\partial x}^{T}BK_{r}r \leq r^{T}h(x), \quad \forall x, r.$$

 $^5$  If this is not the case, the library  $Z(\cdot)$  can be simply extended to include any additional functions appearing in the reference model.

<sup>6</sup>We use a variation of passivity, sometimes referred to as cyclo-passivity, where nonnegativity of the storage function is not required.

The above dissipation inequality holds if and only if [22], [23, Prop. 4. 1. 2],

$$\frac{\partial S}{\partial x}^{T}(x)(A+BK)Z(x) \le 0 \tag{22}$$

and

$$\frac{\partial S}{\partial x}^T B K_r = h^T(x). \tag{23}$$

Suppose that the gradient of the storage function can be written as a linear combination of the functions in the library, i.e.  $\frac{\partial S}{\partial x} = MZ(x)$  fo some matrix  $M \in \mathbb{R}^{n \times s}$ . Similarly, we write the output as h(x) = NZ(x) with  $N \in \mathbb{R}^{m_r \times s}$ . The conditions (22)-(23) are then satisfied if

$$Z^{T}(x)M^{T}(A+BK)Z(x) \le 0 \tag{24}$$

and

$$M^T B K_r = N^T. (25)$$

Let

$$\mathcal{M} := \{ M \mid M \frac{\partial Z}{\partial x} = \frac{\partial Z}{\partial x}^T M^T, \quad \forall x \}.$$
 (26)

Then the set of desired controlled system is specified in terms of  $F \equiv A + BK$  and  $F_r \equiv BK_r$  as

$$\mathcal{F}_{\text{des}} := \{ \begin{bmatrix} F & F_r \end{bmatrix} : Z(x)^T M^T F Z(x) \le 0, \\ M^T F_r = N^T, \ M \in \mathcal{M}, \ N \in \mathbb{R}^{m_r \times s} \}. \quad (27)$$

Note that the inequality in (27) corresponds to (24), the equality corresponds to (25), and the constraint  $M \in \mathcal{M}$  is included to ensure that MZ(x) can be written as a gradient of a function  $S(\cdot)$ . Now, Theorem 11 yields the following data-dependent program:

find 
$$F^\star \in \mathbb{R}^{n \times s}, F_r^\star \in \mathbb{R}^{n \times m_r}, K \in \mathbb{R}^{m \times s}, K_r \in \mathbb{R}^{m \times m_r}$$
 s.t.

$$\operatorname{im} \begin{bmatrix} F^{\star} & F_{r}^{\star} \\ I_{s} & 0 \\ K & K_{r} \end{bmatrix} \subseteq \operatorname{im} \begin{bmatrix} X_{1} \\ Z_{0} \\ U_{0} \end{bmatrix}$$

$$[F^{\star} & F_{r}^{\star}] \in \mathcal{F}_{\operatorname{des}} \text{ in (27)}.$$
(28)

Note that the above program does not contain any model information apart from the library  $Z(\cdot)$ . By tweaking the above program and putting in some additional effort, we obtain the following result as a special case.

**Corollary 14** Let  $M \in \mathcal{M}$ . Suppose that there exist  $G_1 \in \mathbb{R}^{N \times s}$ ,  $G_2 \in \mathbb{R}^{N \times m_r}$ , and  $\Theta \in \mathbb{R}^{n \times n}$  such that

$$\begin{bmatrix} I_s & 0 \end{bmatrix} = Z_0 \begin{bmatrix} G_1 & G_2 \end{bmatrix}. \tag{29a}$$

$$X_1 G_1 - \Theta M = 0, \tag{29b}$$

$$\Theta + \Theta^T \le 0. \tag{29c}$$

Then the control law  $u = Kx + K_r r$  with  $K = U_0 G_1$  and  $K_r = U_0 G_2$ , renders the controlled system (15) passive from input r to output  $y := G_2^T X_1^T M Z(x)$ . Moreover, a storage function certifying passivity is given by

$$S(x) = \int_0^1 x^T M Z(tx) dt. \tag{30}$$

Remark 15 We briefly comment on the feasibility of (29). The equality constraint (29a) is feasible if and only if  $Z_0$  has full row rank. The equality constraint (29b) holds for some  $\Theta$  if and only if  $\ker M \subseteq \ker X_1G_1$ . Overall, for a given M, the constraints form an LMI in variables  $G_1$  and  $\Theta$ , while  $G_2$  is only used to shape the passive output. Hence, one needs to search for a matrix M in class M such that the corresponding LMI in (29) is feasible.

We note that after applying the control law stated in Corollary 14, the resulting controlled system (15) takes the form

$$x^{+} = X_{1}G_{1}Z(x) + X_{1}G_{2}r = \Theta MZ(x) + X_{1}G_{2}r,$$
  
 $y = G_{2}^{T}X_{1}^{T}MZ(x).$ 

Noting that  $M \in \mathcal{M}$ , we can write  $MZ(x) = \frac{\partial S}{\partial x}$  for some function  $S : \mathbb{R}^n \to \mathbb{R}$ . Hence, the controlled system simplifies to

$$x^{+} = \Theta \frac{\partial S}{\partial x} + X_1 G_2 r, \quad y = (X_1 G_2)^T \frac{\partial S}{\partial x}.$$

By using (29c), it turns out that the above controlled system admits a port-Hamiltonian representation with S serving as the Hamiltonian [23, Ch. 6]. The fact that port-Hamiltonian systems are passive proves the claim made in Corollary 14; namely,

$$\frac{\partial S}{\partial x}^{T} x^{+} = \frac{\partial S}{\partial x}^{T} \Theta \frac{\partial S}{\partial x} + \frac{\partial S}{\partial x}^{T} X_{1} G_{2} r \leq \frac{\partial S}{\partial x}^{T} X_{1} G_{2} r = r^{T} y,$$

where we used (29c) to write the inequality. The explicit form of the storage function in (30) follows from the Hadamard lemma [24, Ch. 2], noting  $\frac{\partial S}{\partial x} = MZ(x)$ . It is worth mentioning that a systematic way for feedback passivation of nonlinear systems is in general missing even in the model based regime. Specialising the class of passive systems to port-Hamiltonian systems allows to write the more tractable conditions (29) in place of (28). For linear systems, the two classes coincide. In particular, restricting the results to linear systems Z(x) = x and positive definite storage functions, the class (26) reduces to positive definite  $n \times n$  matrices and the constraints in (29) reduce to

$$[I_s \quad 0] = Z_0 [G_1 \quad G_2],$$

$$X_1 G_1 M^{-1} + M^{-1} (X_1 G_1)^T \le 0, \quad M > 0.$$
 (31)

It is easy to show that the above inequalities can be equivalently stated as the following linear matrix inequalities

$$0 = Z_0 G_2, \quad X_1 Q + (X_1 Q)^T \le 0, \quad Z_0 Q = (Z_0 Q)^T > 0,$$

with variables Q and  $G_2$ . If the above LMI is feasible, then (31) is satisfied with  $M:=(Z_0Q)^{-1}$  and  $G_1:=Q(Z_0Q)^{-1}$ , and the controller  $u=U_0G_1x+U_0G_2r$  renders the linear system passive from input r to output  $y=G_2^TX_1^T(Z_0Q)^{-1}x$ . The underlying storage function in (30) takes the quadratic form

$$S(x) = \int_0^1 t \, x^T M x \, dt = \frac{1}{2} x^T M x = x^T (Z_0 Q)^{-1} x.$$

## IV. CONCLUSIONS

In this note, we have introduced a comprehensive, versatile, and unifying framework for direct data-driven control of nonlinear systems. This framework addresses the sparsity observed in the literature and put forward systematic procedures for synthesizing control algorithms directly from data. By adopting a meta-framework approach, we have shown how several existing results can be incorporated and extended, enhancing the application of data-driven methodologies to various control scenarios including nonlinear stabilization, nonlinear oscillator design, model reference control, and passivizing feedbacks. The examples discussed demonstrate not only the applicability of the proposed framework, but also its potential to foster further advancements in data-driven control research. As the challenges of nonlinear systems and the data they generate continue to grow, the need for effective data-driven control solutions becomes increasingly critical. While the discussed framework is well-positioned to meet these challenges, there is still a long way to go in providing complete answers to the complexities inherent in nonlinear data-driven control.

#### REFERENCES

- M. C. Campi, A. Lecchini, and S. M. Savaresi, "Virtual reference feedback tuning: a direct method for the design of feedback controllers," *Automatica*, vol. 38, no. 8, pp. 1337–1346, 2002.
- [2] M. Tanaskovic, L. Fagiano, C. Novara, and M. Morari, "Data-driven control of nonlinear systems: An on-line direct approach," *Automatica*, vol. 75, pp. 1–10, 2017.
- [3] M. Fliess and C. Join, "Model-free control," *International Journal of Control*, vol. 86, no. 12, pp. 2228–2252, 2013.
- [4] P. Tabuada, W.-L. Ma, J. Grizzle, and A. D. Ames, "Data-driven control for feedback linearizable single-input systems," in 2017 IEEE 56th Annual Conference on Decision and Control (CDC). IEEE, 2017, pp. 6265–6270.
- [5] L. Fraile, M. Marchi, and P. Tabuada, "Data-driven stabilization of SISO feedback linearizable systems," arXiv preprint arXiv:2003.14240, 2020.
- [6] L. Huang, J. Lygeros, and F. Dörfler, "Robust and kernelized dataenabled predictive control for nonlinear systems," *IEEE Transactions* on Control Systems Technology, 2023.
- [7] M. Korda and I. Mezić, "Linear predictors for nonlinear dynamical systems: Koopman operator meets model predictive control," *Automatica*, vol. 93, pp. 149–160, 2018.
- [8] J. L. Proctor, S. L. Brunton, and J. N. Kutz, "Dynamic mode decomposition with control," SIAM Journal on Applied Dynamical Systems, vol. 15, no. 1, pp. 142–161, 2016.
- [9] C. De Persis and P. Tesi, "Formulas for data-driven control: Stabilization, optimality, and robustness," *IEEE Transactions on Automatic Control*, vol. 65, no. 3, pp. 909–924, 2019.
- [10] —, "Learning controllers for nonlinear systems from data," Annual Reviews in Control, p. 100915, 2023.
- [11] A. Bisoffi, C. De Persis, and P. Tesi, "Data-based stabilization of unknown bilinear systems with guaranteed basin of attraction," *Systems & Control Letters*, vol. 145, p. 104788, 2020.
- [12] Z. Yuan and J. Cortés, "Data-driven optimal control of bilinear systems," IEEE Control Systems Letters, vol. 6, pp. 2479–2484, 2022.
- [13] T. Dai and M. Sznaier, "A semi-algebraic optimization approach to data-driven control of continuous-time nonlinear systems," *IEEE Control Systems Letters*, vol. 5, no. 2, pp. 487–492, 2020.
- [14] M. Guo, C. De Persis, and P. Tesi, "Data-driven stabilization of nonlinear polynomial systems with noisy data," *IEEE Transactions on Automatic* Control, vol. 67, no. 8, pp. 4210–4217, 2021.
- [15] R. Strässer, J. Berberich, and F. Allgöwer, "Data-driven control of nonlinear systems: Beyond polynomial dynamics," in 2021 60th IEEE Conference on Decision and Control (CDC). IEEE, 2021, pp. 4344– 4351.
- [16] M. Alsalti, J. Berberich, V. G. Lopez, F. Allgöwer, and M. A. Müller, "Data-based system analysis and control of flat nonlinear systems," in 2021 60th IEEE Conference on Decision and Control (CDC). IEEE, 2021, pp. 1484–1489.

- [17] C. De Persis, M. Rotulo, and P. Tesi, "Learning controllers from data via approximate nonlinearity cancellation," *IEEE Transactions on Automatic Control*, 2023.
- [18] H. van Waarde, J. Eising, H. Trentelman, and K. Camlibel, "Data informativity: a new perspective on data-driven analysis and control," *IEEE Transactions on Automatic Control*, vol. 65, no. 11, pp. 4753– 4768, 2020.
- [19] V. Breschi, C. De Persis, S. Formentin, and P. Tesi, "Direct data-driven model-reference control with Lyapunov stability guarantees," in 2021 60th IEEE Conference on Decision and Control (CDC). IEEE, 2021, pp. 1456–1461.
- [20] J. Wang, S. Baldi, and H. J. van Waarde, "Necessary and sufficient conditions for data-driven model reference control," arXiv preprint arXiv:2310.11159, 2023.
- [21] A. Padoan, J. Coulson, and F. Dörfler, "Controller implementability: a data-driven approach," in 2023 62nd IEEE Conference on Decision and Control (CDC). IEEE, 2023, pp. 6098–6103.
- [22] D. Hill and P. Moylan, "The stability of nonlinear dissipative systems," IEEE transactions on automatic control, vol. 21, no. 5, pp. 708–711, 1976.
- [23] A. Van der Schaft, L2-gain and passivity techniques in nonlinear control. Springer, 2016.
- [24] J. Nestruev, Smooth manifolds and observables. Springer, 2003, vol. 220.